

### PressSense Flexible White Opaque Vinyl with permanent Block-Out adhesive.

#### Characteristics

A 3.4 mil matte white flexible calendered vinyl film coated with a permanent gray acrylic pressure sensitive adhesive on a 90# layflat liner. The gray adhesive is designed to provide block-out of existing graphics. The vinyl film accepts a variety of UV curable and solvent based screen ink.

#### Application

This product is designed for permanent decals, nameplates, product markings and point-of-purchase decals requiring complete opacity.

#### Thickness

Film – 3.4 mils  
Adhesive – 0.8 to 1.0 mil.  
Liner – 6.7 mils.  
(Thickness variance +/- 10%)

#### Dimensional Stability

Good.

#### Temperature Ranges

Minimum application temperature +50°F.  
Service temperature is -40°F to +200°F.

#### Expected Exterior Exposure

Up to 2 years.

#### Adhesion

To stainless steel - 40 oz/in.  
PSTC-1 with 24 hour dwell at 70° F and 50% relative humidity.  
Typical values. Individual values may vary. Test thoroughly before production.

#### Water Resistance

Limited immersion resistance. Test for specific application.

#### Humidity Resistance

Good.

#### Storage Stability

1 year shelf life when stored at 70°F and 50% relative humidity.

Typical properties should be referenced as a general guide, not as a guarantee. Testing should be completed on material based on individual customer systems, efficiencies, temperatures and applications as properties can change based on customer production methods.